




Model	GB-1001	GB-5005	GB-8008
			
Description	GB-1001 rack mountable server	Half rack containing 5 servers, 2 APC switches, network switch and load balancer	Full rack containing 12 servers, 3 APC switches, network switch and load balancer
Maximum Document Capacity	Up to 1.5 million documents* or 100 GB	Up to 5 million documents* or 450 GB	Up to 15 million documents* or 1350 GB
Crawled Document Size Limits	2.5 MB for HTML, 30 MB for other file types	2.5 MB for HTML, 30 MB for other file types	2.5 MB for HTML, 30 MB for other file types
Traffic	300 queries/minute	300 queries/minute	300 queries/minute
Dimensions	Height 3.5" (2U) x Width 19.0" x Depth 25.13"	34"H x 24"W x 36"D	84"H x 24"W x 36.4"D
Power	Voltage: 90V~250V Frequency: 50~60 Hz, Maximum input line current: 6A@120V or 3A@240V	Voltage: 100V~120V Frequency: 50~60 Hz Requires 2 dedicated 115 VAC branch circuits with NEMA 5-15 outlet Maximum current draw is 15 Amps per circuit	Voltage: 100V~120V Frequency: 50~60 Hz Requires 3 dedicated 115 VAC branch circuits with NEMA 5-15 outlet Maximum current draw is 15 Amps per circuit
Thermal	13700 BTU/hr 4 KW continuous dissipation 1.2 tons of refrigeration load	7830 BTU/hr 2.3 KW continuous dissipation .67 tons of refrigeration load	17500 BTU/hr 5.1 KW continuous dissipation 1.5 tons of refrigeration load
Other	56K external data/fax modem for remote diagnostics	56K external data/fax modem for remote diagnostics	56K external data/fax modem for remote diagnostics

* Actual document capacity depends on license purchased

Ordering Information: www.google.com/enterprise/